

# MODEL 883 ADV-XTREME

EXTERIOR HIGH SPEED, HIGH PERFORMANCE FABRIC DOOR



## Fast acting, rugged fabric door

### HIGH PERFORMANCE, LOW MAINTENANCE DESIGN

- Strutted design allows for quick section replacement while reducing curtain deflection under pressure
- Springless design requires minimal interruption for maintenance
- Direct-mounted gear drive minimizes wear and tear
- Variable frequency drive eliminates sudden jolts from door start/stop
- Patent-pending breakaway system design with impact detection and push button self-repair

### RUGGED FABRIC CONSTRUCTION

- Ideal for exterior applications
- Rough environment interior applications

### INSTALLER FRIENDLY

- Pre-assembled sub-assemblies for easier installation
- Plug and play wiring reduces need for licensed electrician

### APPLICATIONS

- Manufacturing/Heavy Manufacturing
- Warehouse/Distribution
- Auto/Transit
- Food and Beverage



# MODELS 883 ADV-XTREME

EXTERIOR HIGH SPEED, HIGH PERFORMANCE FABRIC DOOR

## STANDARD FEATURES OVERVIEW

### CONSTRUCTION


<b>OPENINGS</b>	Interior/Interior, Exterior/Interior
<b>MAX HEIGHT</b>	15'
<b>MAX WIDTH</b>	16'
<b>MAX OPENING SPEED</b>	Up to 65" per second
<b>MAX CLOSING SPEED</b>	Up to 40" per second
<b>BREAK AWAY SELF RESET</b>	Yes
<b>WIND LOAD*</b>	Up to 4.0 psf
<b>WIND STRUT</b>	2" strut standard
<b>CURTAIN MATERIAL</b>	3 layers of PVC-coated polyester with 2 layer of polyester weave
<b>VISION</b>	20" high windows spaced evenly across width of door
<b>OPERATION</b>	Direct drive motor and gearbox system with a door stop safety device
<b>CONTROL PANEL</b>	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable field disconnect
<b>OBSTRUCTION SAFETY DETECTION</b>	Infrared sensors mounted in-plane to the door curtain at 18" and 50" - 54" from floor
<b>REVERSING SAFETY EDGE</b>	Wireless reversing edge
<b>AVAILABLE SUPPLY VOLTAGES</b>	208-245V AC 3PH/60HZ; 440-480V AC 3PH/60HZ, 575V AC 3PH/60HZ (requires transformer)
<b>HINGED GUIDES</b>	Provide easy access for maintenance

\*Wind load is the ultimate pressure tested at door width of 16'.

### OPTIONS

- **20" high windows** – spaced evenly across width of door
- **Multiple actuation options** – push button, motion detector, radio control, key switch, pull switch, loop detector, treadle switch
- **Signaling devices** – red/green LED warning light, horn/strobe combination, rotating warning light
- **Stainless steel guides, hood, motor cover, and head plates**
- **Programmable LED Lighting Package** – 3' tall light bar with red, yellow, green lights

### CURTAIN COLOR OPTIONS



Gray



Orange



Blue



Red

Other colors may be available. See your Wayne Dalton Dealer for details. Actual colors may vary from brochure due to fluctuations in the printing process. Always request a color sample from your Wayne Dalton Dealer for accurate color matching.

Standard color for guides and bottom bar is yellow  
Approximately 200 optional RAL powder coat colors are also available.



**Wayne Dalton**  
COMMERCIAL DOORS

2501 S. State Hwy. 121 Bus., Ste 200  
Lewisville, TX 75067

[wayne-dalton.com](http://wayne-dalton.com)



© 2020 Wayne Dalton, a Division of Overhead Door Corporation. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.  
Item W900-1054 04/20