

MODEL 885 ADV-XTREME

EXTERIOR HIGH SPEED, HIGH PERFORMANCE RUBBER DOOR



Tough reinforced rubber door for extreme environments

RUGGED CONSTRUCTION

- Multi-layered, reinforced rubber provides added strength without the weight
- Ideal for harsh exterior conditions with a wind load of up to 27.0 psf
- Nitrile butadiene rubber (NBR) provides resistance to petrochemicals for easy cleaning

HIGH CYCLE, LOW MAINTENANCE DESIGN

- Springless design requires minimal interruption for maintenance
- Patent-pending, breakaway system design with impact detection and push button self-repair
- Direct-mounted gear drive minimizes wear and tear
- Variable frequency drive eliminates sudden jolts from door start/stop

INSTALLER FRIENDLY

- Pre-assembled sub-assemblies for easier installation
- Plug-and-play wiring reduces the need for a licensed electrician

APPLICATIONS

- Manufacturing/Heavy Manufacturing
- Warehouse Distribution
- Large Opening
- Mining
- Parking Garages
- Auto/Transport



MODELS 885 ADV-XTREME

EXTERIOR HIGH SPEED, HIGH PERFORMANCE RUBBER DOOR

STANDARD FEATURES OVERVIEW

CONSTRUCTION

OPENINGS	Exterior
MAX HEIGHT	30'
MAX WIDTH	30'
MAX OPENING SPEED	Up to 50" per second
MAX CLOSING SPEED	Up to 40" per second
BREAK AWAY SELF RESET	Yes
WIND LOAD*	Up to 27.0 psf
HEADROOM (WITH HOOD)	Up to 30' tall: 23.5", Up to 14' tall: 18", up to 20' tall: 20"
CURTAIN MATERIAL	5 Layers of NRB rubber with 4 layers of polyester weave
VISION	Optional 10" x 20" windows (maximum quantity depends on door size)
CURTAIN LOCK	Standard
OPERATION	Direct drive motor and gearbox system with a door stop safety device
CONTROL PANEL	Variable frequency drive NEMA 4X cULus listed. Onboard self diagnostic and service reminder. Built-in padlockable field disconnect
OBSTRUCTION SAFETY DETECTION	Infrared sensors mounted in-plane to the door curtain at 8" and 50" - 54" from floor
REVERSING SAFETY EDGE	Wireless reversing edge
AVAILABLE SUPPLY VOLTAGES	208-245V AC 3PH/60HZ; 440-480V AC 3PH/60HZ, 575V AC 3PH/60HZ (requires transformer)

*Wind load is the ultimate pressure tested at door width of 19'.



Continuous curtain locks on both edges (shown outside the guide for clarification).

OPTIONS

- **20" high windows** – spaced evenly across width of door
- **Multiple actuation options** – push button, motion detector, radio control, key switch, pull switch, loop detector, treadle switch
- **Signaling devices** – red/green LED warning light, horn/strobe combination, rotating warning light
- **Programmable LED Lighting Package** – 3' tall light bar with red, yellow, green lights

CURTAIN COLOR OPTIONS



Black
(Standard)



Blue

Other colors may be available. See your Wayne Dalton Dealer for details. Actual colors may vary from brochure due to fluctuations in the printing process. Always request a color sample from your Wayne Dalton Dealer for accurate color matching.

Standard color for guides and bottom bar is yellow. Approximately 200 optional RAL powder coat colors are also available.



Wayne Dalton
COMMERCIAL DOORS

2501 S. State Hwy. 121 Bus., Ste 200
Lewisville, TX 75067

wayne-dalton.com



© 2020 Wayne Dalton, a Division of Overhead Door Corporation. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.
Item W900-1056 04/20