

MODEL 888 ADV-XTREME

EXTERIOR HIGH SPEED, HIGH PERFORMANCE METAL DOOR



Power, security, and durability

HIGH PERFORMANCE DESIGN

- Springless design for over 1 million cycles and requires minimal interruption for maintenance
- Gravity drive system coupled with variable frequency drive eliminates sudden jolts from door start/stop
- Direct-mounted gear drive minimizes wear and tear

DURABLE CONSTRUCTION

- Dual-walled, solid aluminum curtain for security and privacy
- Steel head plate utilizes high strength, durable rollers to prevent metal curtain contact and provides smooth operation

INSTALLER FRIENDLY

- Fully-assembled curtain arrives pre-wrapped in head plate and trusses, ready for installation
- Completely hinged guide
- Pre-wired motor connection and plug and play accessories reduces the need for a licensed electrician

SAFETY FOCUSED

- Patent-pending integrated curtain monitoring device ensures the door has a redundant system to monitor the position of the door
- Safety light curtain minimizes contact with objects in the doorway
- Monitored wireless reversing edge

APPLICATIONS

- Parking garages
- Manufacturing
- Auto dealerships



*Up to 50 psf with optional vision panels.

MODELS 888 ADV-XTREME


EXTERIOR HIGH SPEED, HIGH PERFORMANCE METAL DOOR

STANDARD FEATURES OVERVIEW

CONSTRUCTION

OPENINGS	Exterior
MAX HEIGHT	21'
MAX WIDTH	14'
MAX OPENING SPEED	Up to 70" per second
MAX CLOSING SPEED	Up to 40" per second
WIND LOAD	UP TO 100 [†] psf
OPERATIONAL PRESSURE	Dependent on door size and site condition
CURTAIN MATERIAL	Dual-walled aluminum
OPERATION	Direct drive motor and gearbox system
CONTROL PANEL	Variable frequency drive NEMA 4X cULus listed
OBSTRUCTION	Infrared sensors mounted in-plane to the door curtain at 18" and 50" - 54" from floor
SAFETY DETECTION	
REVERSING SAFETY EDGE	Wireless reversing edge
AVAILABLE SUPPLY VOLTAGES	208-245V AC 3PH/60Hz; 440-480V AC 3PH/60Hz, 575V AC 3PH/60Hz (requires transformer)

*Wind load is the ultimate pressure tested at door width of 15'.
†Up to 50 psf with optional vision panels.



Perforated Slat



Vision Slat

OPTIONS

- **Slim guide** – to reduce jamb side room
- **Multiple actuation options** – push button, motion detector, radio control, key switch, pull switch, loop detector, treadle switch
- **Signaling devices** – red/green LED warning light, horn/strobe combination, rotating warning light
- **Clear anodized slats/bottom bar**
- **Lintel cover**
- **Photo eyes**
- **Programmable LED Lighting Package** – 3' tall light bar with red, yellow, green lights
- **Perforated slat** – up to four slats with 24% open area
- **Vision slat** – up to four slats for vision through the door

COLOR OPTIONS

Guide/Slats/
Bottom bar



Silver powder coat**
(Standard)

Bracket/Hood
Structure



Black powder coat
(Standard)

**Silver powder coat made to mimic anodized aluminum.

Actual colors may vary from brochure due to fluctuations in the printing process. Always request a color sample from your Wayne Dalton Dealer for accurate color matching.

Approximately 200 optional RAL powder coat colors are also available.



Wayne Dalton
COMMERCIAL DOORS

2501 S. State Hwy. 121 Bus., Ste 200
Lewisville, TX 75067

wayne-dalton.com



© 2020 Wayne Dalton, a Division of Overhead Door Corporation. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.
Item W900-1133 04/20