

# MODEL 889 ADV-XTREME

EXTERIOR HIGH SPEED, HIGH PERFORMANCE, FULL-VIEW METAL DOOR



## High speed, visibility, and durability

### HIGH PERFORMANCE DESIGN

- Springless design for over 1 million cycles and requires minimal interruption for maintenance
- Gravity drive system coupled with variable frequency drive eliminates sudden jolts from door start/stop
- Direct-mounted gear drive minimizes wear and tear

### DURABLE CONSTRUCTION

- Full-view door with corrosion-resistant aluminum and clear vision, impact-resistant polycarbonate panels
- Steel head plate utilizes high strength, durable rollers to prevent metal curtain contact and provides smooth operation
- Independently-tested and capable of withstanding pressure of up to 50 psf

### INSTALLER FRIENDLY

- Fully-assembled curtain arrives pre-wrapped in head plate and trusses, ready for installation
- Completely hinged guide
- Pre-wired motor connection and plug and play accessories reduces the need for a licensed electrician

### SAFETY FOCUSED

- Patent-pending integrated curtain monitoring device ensures the door has a redundant system to monitor the position of the door
- Safety light curtain minimizes contact with objects in the doorway
- Monitored wireless reversing edge

### APPLICATIONS

- Auto dealerships
- Retail
- Manufacturing



# MODELS 889 ADV-XTREME


EXTERIOR HIGH SPEED, HIGH PERFORMANCE, FULL-VIEW METAL DOOR

## STANDARD FEATURES OVERVIEW

### CONSTRUCTION

<b>OPENINGS</b>	Exterior
<b>MAX HEIGHT</b>	21'
<b>MAX WIDTH</b>	20'
<b>MAX OPENING SPEED</b>	Up to 80" per second
<b>MAX CLOSING SPEED</b>	Up to 20" per second
<b>WIND LOAD*</b>	Up to 50 psf
<b>CURTAIN MATERIAL</b>	Aluminum and scratch-resistant polycarbonate
<b>VISION</b>	Scratch-resistant polycarbonate panels
<b>OPERATION</b>	Direct drive motor and gearbox system
<b>CONTROL PANEL</b>	Variable frequency drive NEMA 4X cULus listed
<b>OBSTRUCTION</b>	Integrated light curtain
<b>SAFETY DETECTION</b>	
<b>REVERSING SAFETY EDGE</b>	Wireless reversing edge
<b>AVAILABLE SUPPLY VOLTAGES</b>	230V AC 3PH, 460V AC 3PH, 575V AC 3PH

\*Wind load is the ultimate pressure tested at door width of 15'.



Perforated Slat (optional)

### OPTIONS

- **Slim guide available** – to reduce jamb side room
- **Multiple actuation options** – push button, motion detector, radio control, key switch, pull switch, loop detector, treadle switch
- **Signaling devices** – red/green LED warning light, horn/strobe combination, rotating warning light
- **Clear anodized slats/bottom bar**
- **Lintel cover**
- **Photo eyes**
- **Programmable LED Lighting Package** – 3' tall light bar with red, yellow, green lights
- **Perforated slat** – up to four slats with 24% open area

## COLOR OPTIONS

Guide/Slats/  
Bottom bar



Silver powder coat\*\*  
(Standard)

Bracket/Hood  
Structure



Black powder coat  
(Standard)

\*\*Silver powder coat made to mimic anodized aluminum.

Actual colors may vary from brochure due to fluctuations in the printing process. Always request a color sample from your Wayne Dalton Dealer for accurate color matching.

Approximately 200 optional RAL powder coat colors are also available.



**Wayne Dalton**  
COMMERCIAL DOORS

2501 S. State Hwy. 121 Bus., Ste 200  
Lewisville, TX 75067

[wayne-dalton.com](http://wayne-dalton.com)



© 2020 Wayne Dalton, a Division of Overhead Door Corporation. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.  
Item W900-1135 04/20